

NJ Glen UV -1604E / 1804E UV

(EPSON I3200-U1x4)


White / Matte / Hollowed / Bronzing Special UV Integrated Printer



COLOR+WHITE+COLOR+VARNISH
MATTE HOLLOWED BRONZING
Multilayer Printing



Four I3200 Heads



UV Ink

C M Y K (W) +Bronzing Varnish+Matte Varnish



APPLICATIONS: Glass stickers, PVC gift box packaging, light box posters, customized car stickers, background wall cloth, gold paper and silver paper printing, leather printing, high-end gift box printing, food packaging printing, Label printing, operation panel & switch printing etc.

NJ-1604E/1804E UV :	CMYK + W + CMYK	CMYK + W + CMYK + BV	CMYK + W + CMYK + BV + MV
6pass:720x1200dpi	11sqm/h	11sqm/h	11sqm/h
8pass:720x2400dpi	11sqm/h	11sqm/h	11sqm/h

● Technical Specifications

Model	NJ-1604E UV		NJ-1804E UV
Print Head	Four Epson I3200-U1 Print Heads		Four Epson I3200-U1 Print Heads
Printing Technology	Piezoelectric Inkjet		
Acceptable Media	Width	64 in.(1620 mm)	71.6 in.(1820 mm)
	Thickness	Maximum 59 mil(1.5 mm)	Maximum 59 mil(1.5 mm)
	Weight	132 lb.(60 kg)	176 lb.(80 kg)
Printing Width	63 in.(1600 mm)		70.8 in.(1800 mm)
Ink Cartridges	Type	UV Ink	
	Capacity	Continual Ink Supply System (1.5L ink tank)	
	Color	CMYK + W + CMYK CMYK + W + CMYK + BV	CMYK + W + CMYK + BV + MV
Ink Curing Unit	Dual UV LED Lamps (Water Cooling)		
Printing Resolution	Maximum 2400 dpi		
Interface	USB 2.0		
Power Supply	AC 220V ± 10%, 50/60 HZ		
RIP	Onyx / Photoprint		
Dimensions(with stand)	102(W)x27(D)x62(H) in.		110(W)x30(D)x62(H) in.
	(2600(W)x680(D)x1580(H) mm)		(2800(W)x750(D)x1580(H) mm)
Weight(with stand)	705 lb. (320 kg)		750 lb. (340 kg)
Package Dimensions	110(W)x30(D)x35(H) in.		114(W)x30(D)x40(H) in.
	(2800(W)x750(D)x880(H) mm)		(2900(W)x760(D)x1020(H) mm)
Package Weight	750 lb. (340 kg)		793 lb. (360 kg)
Environment	Power on	Temperature: 59 ℉ to 90 ℉ [15℃ to 32℃] (68 ℉ [20℃] / Humidity: 35 to 80% (no condensation)	
	Power off	Temperature: 41 ℉ to 104 ℉ [5℃ to 40℃] / Humidity: 20 to 80% (no condensation)	
Accessories	USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software, etc.		

Multilayer layers printing the output is more delicate



AJ-1604E UV/1804E UV different color pattern collocation application scheme, to meet the needs of different customers, color white color three layer super transparent glass paste using environmental protection materials, green environmental protection; The collocation of multi-layer colors presents different display effects before and after lighting;




Color+ White+ Color + Matte Varnish + Hot Stamping Varnish, Perfect print output put, Applied to various types of glass decorative stickers and personalized packaging material printing, one-time printing, convenient and efficient.



4 ESOPN I3200-U1 HEADS

With Epson Authorized 4*I3200-U1 heads , minimal 3.5pl variable ink droplet UV printer.



Installs a LED light panel, it helps our customer to check the front-lit or back-lit print quality before the order finish.



The automatic moisturizing and cleaning system not only protects the print head, but also ensures the smoothness of the ink-flow .




High quality servo motor with good stability and long life.



External power supply, intelligent rolling system.

3-5 layers Printing technology



Water Cooling drying technology



1.5L bulky ink bottle with lack of ink alarm system represents the advanced concept of industrial application



Dual THK high-precision mute rail.



The pinch roller uses 3 in one type and each pinch roller keeps in a tight and closer distance, it helps the media feeding more smoothly and reduces wrinkle issues.



NEGI SIGN SYSTEMS & SUPPLIES CO.

Mumbai : 301, Shivam Chambers, Next To Sahara, S.V. Road, Goregaon west, Mumbai-400104, Tel : 022-61566000
 Delhi : C-75, DDA Sheds, Okhla Industrial Area, Phase-1, New Delhi- 110020, Tel : 011-49139900
 E-mail : sales@negisign.com, Website : www.negisign.com
 Whats app : 8433908690

