

NJ Glen UV RTR-1602 / 1802

Economical UV roll to roll printer (2*I1600-U1) I3200-U1 optional



UV Ink



I1600-U1

CMYK + CMYK

I1600-U1

W + CMYK

* 1.6m/1.8m Double I1600-U1 Print Heads Speed (I3200-U1 heads optional)

CMYK - 720*600dpi 4pass	25 m ² /h
CMYK - 720*900dpi 6pass	21 m ² /h
CMYK - 720*1200dpi 8pass	17 m ² /h



APPLICATIONS : light box posters, car stickers, advertising hoardings, golden and silver paper, leather printing, high-end gift boxes, food packaging, labels, operation panel and switch printing, etc.

CMYK

720x900dpi 21 sqm/h(6pass)

720x1200dpi 17 sqm/h(8pass)

W+CMYK

720x900dpi 11 sqm/h(6pass)

720x1200dpi 8 sqm/h(8pass)

Technical Specifications

Model	NJ-1602UV	NJ-1802UV	
Print Head	Double I1600-U1 Print Heads (I3200-U1 Optional)		
Printing Technology	Piezoelectric Inkjet		
Acceptable Media	Width	63.7 in.(1620 mm)	71.6 in.(1820 mm)
	Thickness	Maximum 59 mil(1.5 mm)	
	Weight	176 lb.(80 kg)	176 lb.(80 kg)
Printing Width	63 in.(1600 mm)	70.8 in.(1800 mm)	
Ink Cartridges	Type	UV Ink	
	Ink Supply	Bulk ink supply system with 500ml ink tank	
	Color	CMYK / W+CMYK	
Printing Resolution	Maximum 2400 dpi		
Speed	CMYK	6pass (720*900dpi) 21 m ² /h	
	W+CMYK	6pass (720*900dpi) 11 m ² /h	
Curing Unit	Water-cooling UV lamp		
Interface	Ethernet		
Power Supply	AC 220V ± 10%, 50/60 HZ		
Dimensions(with stand)	102(W)x30(D)x62(H) in.	110(W)x30(D)x62(H) in.	
	(2800(W)x680(D)x1580(H) mm)	(2800(W)x750(D)x1580(H) mm)	
Weight(with stand)	617 lb. (280 kg)	661 lb. (300 kg)	
Packing Size	110(W)x30(D)x30(H) in.	114(W)x30(D)x30(H) in.	
	(2800(W)x760(D)x760(H) mm)	(2900(W)x760(D)x760(H) mm)	
Packing Weight	661 lb. (300 kg)	705 lb. (320 kg)	
Environment	Power on	Temperature: 59 ™ to 90 ™ [15 ™ to 32 ™] / Humidity: 35 to 80% (no condensation)	
	Power off	Temperature: 41 ™ to 104 ™ [5 ™ to 40 ™] / Humidity: 20 to 80% (no condensation)	

Two-layer printing technology for color conversion

The 1st layer

White Ink

The 2nd layer

Color Layer




CMYK

W+CMYK

- Leadshine DC Servo Motor
- THK high precision mute rail
- Igus mute drag chain, quite working environment guaranteed
- Automatic up-and-down capping station, protects the print head more effectively

Two Epson I1600-U1 head array (I3200 heads Optional)



Min 3.5pl Variable Ink Droplet

- Equipped with two I1600 print heads, 3.5pl ultra-small ink droplets
- 1.6m/1.8m UV roll to roll printer dedicated for white + color printing
- Scientific head array, high-precision bottom plate, craftsmanship of quality
- Light weight and compact design, saves workshop space



500ml large capacity ink supply system



High quality imported THK high precision guide rail



Moisturizing cleaning assembly



Automatic take-up



LED backlight



Adjustable pinch rollers



NEGI SIGN SYSTEMS & SUPPLIES CO.

Mumbai : 301, Shivam Chambers, Next To Sahara, S.V. Road, Goregaon west, Mumbai-400104, Tel : 022-61566000

Delhi : C-75, DDA Sheds, Okhla Industrial Area, Phase-1, New Delhi- 110020, Tel : 011-49139900

E-mail : sales@negisign.com, Website : www.negisign.com

Whats app : 8433908690

