

MUTOH

ECO-SOLVENT PRINTER



XpertJet

Powered by

AccuFINE
Mutoh Print Heads



Eco-Solvent
Inks



CMYK

1641SR Pro

built for



PROFESSIONALS

The MUTOH XpertJet 1641 SR Pro 64" Eco-Solvent Single head, 4-color (CMYK) printer builds upon MUTOH's made Japan reputation and delivers superior print quality and outstanding speeds at an affordable price. It is powered by ONYX RIP Center genuine RIP Software. ONYX RIP optimizes all of the capabilities the XPJ-1641 SR Pro has to offer and produces the best-possible gradients, skin tones and vivid colors. This printer features MUTOH's new Accufine Print Head, which achieves best-in-class dot placement accuracy and an increased nozzle row length for 35% faster print speeds. The XPJ-1641 SR Pro is paired with MUTOH's GREENGUARD Gold certified MS41 Eco-Solvent ink, suitable for use in sensitive environments such as hospitals, child care facilities and more, all while providing user a larger color gamut, outstanding durability and improved dotgain.



WRAPS



SIGNAGE



WINDOW VINYL



DECALS

MUTOH

NEW ACCUFINE
HD PRINTHEAD

IMPROVED
DRYER SYSTEM

ONYX
GENUINE RIP SOFTWARE

AUTOMATIC
ALIGNMENTS

INTERNAL
LED LIGHTING

Xpertjet 1641SR Pro

Powered by Genuine ONYX RIP Center software

ONYX

AccuFINE
MUTOH Print Heads



Internal LED Lighting



AccuFine print head



Multi-stage pressure mechanism



Media Flange for improved handling

XPERTJET 1641SR Pro SPECIFICATIONS

Printing systems	Drop-on-demand Micro Piezo Inkjet Technology
Print head height	Four-level adjustment: 1.5mm , 2.0mm , 2.5mm , 4.0mm
Print head	1
Max print resolution	1200x1200 dpi
Print modes	1200 / 900 / 600 /300 dpi
Media width	64"
Media capacity	ø5.9" dia / 2" & 3" cores / Roll media 30 kg or less
Max media thickness	Low1-0.3mm , Low2 -0.8mm, Mid -1.3mm, High - 2.8mm
Max printable width	64 inch
Take-up system	Optional
RIP software	ONYX RIP Center

Ink	Type	Eco-Solvent ink
	Ink Set	4 colors (C, M, Y, K)
	Volume	1L ink bags
	No. of slots	4
Interface	Gigabit-Ethernet (1000 BASE-T)	
Power Requirements	AC 100 -120V ± 10% , 50/60Hz ± 1Hz	
Printable Environment	Temperature:22°C-32°C Humidity: 40-60% (non condensing)	
Power Consumption	Main:Operation status 77W or less Standby: 52W or less	
Dimensions (WxDxH)	Printer including stand: 108.26"x35.23"x56.22" cover closed	
Weight	Body: 140 kg Stand: 32 kgs	

NEGI

Negi Sign Systems & Supplies Co.

Mumbai Head Office

301, Shivam Chambers, S. V. Road, Goregaon West, Mumbai- 400104.

Delhi Regional Office

C-75, DDA Sheds, Okhla Industrial Area, Phasel, New Delhi- 110020.

: 8433908690

Tel no: 022- 61566000
Tel no: 011- 49139900

Email id : sales@negisign.com

Website : www.negisign.com

